

COMET ORB – GNSS SATELLITES ORBIT DETERMINATION IMPROVEMENTS AND APPLICATIONS

INTRODUCTION TO GNSS POSITIONING METHODS

MARIE ANSART – MARIE.ANSART@THALESALENIASPACE.COM



TABLE OF CONTENT

- ❑ Basis of GNSS positioning
- ❑ Absolute and relative techniques
- ❑ Precise positioning
- ❑ Hybridization – sensor fusion
- ❑ GNSS LEO constellations

PROPRIETARY INFORMATION

This document is not to be reproduced, modified, adapted, published, translated in any material form in whole or in part nor disclosed to any third party without the prior written permission of Thales Alenia Space.
© 2024 Thales Alenia Space All rights reserved

BASIS OF GNSS POSITIONING

/// 3

Date: 21/01/2025

Ref:

Template: 83230347-DOC-TAS-EN-011

PROPRIETARY INFORMATION

This document is not to be reproduced, modified, adapted, published, translated in any material form in whole or in part nor disclosed to any third party without the prior written permission of Thales Alenia Space.

© 2024 Thales Alenia Space All rights reserved


THALES ALENIA SPACE LIMITED DISTRIBUTION

ThalesAlenia
Space
a Thales / Leonardo company

REFERENCE FRAME AND TIME SCALE


/// Reference frame

- Position and velocity should be given relatively to a reference frame or coordinate system
 - GPS: WGS84
 - GALILEO: GTRF



/// Reference time scale

- Time should be given with respect to a reference time scale (steered to UTC)
 - GPS: GPST
 - GALILEO: GST



COMPUTATION OF 3D POSITION


/// 3 equations, 3 unknowns

! x_u, y_u, z_u ('u' for user)

$$\sqrt{(x_1 - x_u)^2 + (y_1 - y_u)^2 + (z_1 - z_u)^2} = D1$$

$$\sqrt{(x_2 - x_u)^2 + (y_2 - y_u)^2 + (z_2 - z_u)^2} = D2$$

$$\sqrt{(x_3 - x_u)^2 + (y_3 - y_u)^2 + (z_3 - z_u)^2} = D3$$



MINIMUM OF 4 SATELLITES FOR GNSS APPLICATIONS


/// The satellite clock offset with respect to reference time scale is given in the navigation message while the distance due to user clock bias should be added as a fourth unknown (b_u)

$$\sqrt{(x_1 - x_u)^2 + (y_1 - y_u)^2 + (z_1 - z_u)^2} + b_u = D1$$

$$\sqrt{(x_2 - x_u)^2 + (y_2 - y_u)^2 + (z_2 - z_u)^2} + b_u = D2$$

$$\sqrt{(x_3 - x_u)^2 + (y_3 - y_u)^2 + (z_3 - z_u)^2} + b_u = D3$$

$$\sqrt{(x_4 - x_u)^2 + (y_4 - y_u)^2 + (z_4 - z_u)^2} + b_u = D4$$



PERTURBATIONS THAT INDUCE SIGNAL DELAYS

/// The signal is impacted by various sources:

- / Ionosphere
- / Troposphere
- / Interference
 - Involuntary
 - Jamming
 - Spoofing
- / Multipath
- / Receiver Noise
- / Hardware bias
- / Clock relativistic effect
- / ...

ABSOLUTE AND RELATIVE TECHNIQUES

/// 8
Date: 21/01/2025

Ref:

Template: 83230347-DOC-TAS-EN-011

PROPRIETARY INFORMATION

This document is not to be reproduced, modified, adapted, published, translated in any material form in whole or in part nor disclosed to any third party without the prior written permission of Thales Alenia Space.

© 2024 Thales Alenia Space All rights reserved

THALES ALENIA SPACE LIMITED DISTRIBUTION

ABSOLUTE AND RELATIVE TECHNIQUES

/// Absolute techniques include: SPP, SBAS, PPP, PPP-RTK

/ SPP: Standard Point Positioning (stand alone method)

/ SBAS: Satellite Based Augmentation System (used for aviation)

/ PPP and PPP-RTK: precise positioning methods (down to centimeter-level performance)

/// Relative techniques include: DGNSS (DGPS, DBAS, RTK)

/ DGPS: every country deploys radio-beacons along the coasts to help Maritime Navigation up to a range of 100km. These reference stations transmit the differential corrections to the boats.

/ DBAS: equivalent of DGPS but for aviation and with reference stations in a specific area

/ RTK: dense grid of stations to provide differential corrections that include all contributors

PRECISE POSITIONING

Date: 21/01/2025

Ref:

Template: 83230347-DOC-TAS-EN-011

PROPRIETARY INFORMATION

This document is not to be reproduced, modified, adapted, published, translated in any material form in whole or in part nor disclosed to any third party without the prior written permission of Thales Alenia Space.

© 2024 Thales Alenia Space All rights reserved

THALES ALENIA SPACE LIMITED DISTRIBUTION

CHOICE OF APPROACH FOR METER-LEVEL PERFORMANCE

/// 2 options

/ **OSR (Observation State Representation)** approach: correction at pseudo range level

/ **SSR (State Space Representation)** approach: distinction between corrections for orbit, clock and ionosphere)


- Satellite Ephemeris Correction Parameters;
- Satellite Time Correction Parameters;
- Code Phase Measurement Correction Parameters;
- Ionospheric Delay Correction Parameters

EXAMPLE OF QZSS SLAS (SUB-METER LEVEL AUGMENTATION SERVICE)

/// Use of OSR (Observation State Representation) method

■ DGNSS (Differential GNSS)

- Principle: the error for a user and for a known fixed monitoring station is similar if the user is close enough to the station.
- Correction at pseudo range level (errors not segregated by source)



User algorithm

OVERVIEW OF SSR METHOD

///Use of SSR (State Space Representation) method

■ In SSR approach, corrections are sent per contributor: satellite orbit and clock and ionosphere

- The SBAS receiver applies the GNSS navigation message plus the broadcast SBAS corrections on the top of it:

- Satellite Orbit Corrections


$$r_{SBAS}^i = r_{NAV}^i + LTC_{ORB}$$

(LTC = Long-Term Corrections ;
FC = Fast Corrections)

- Satellite Clocks Corrections

$$b_{SBAS}^i = b_{NAV}^i + FC_{CLK} + LTC_{CLK}$$

- The SBAS needs to provide an independent and better Ionosphere Model than the classical navigation message



CHOICE OF APPROACH FOR CENTIMETER-LEVEL PERFORMANCE

- PPP** (global approach): Kalman filter to estimate all the parameters including the phase ambiguities
- RTK** (local approach): regional application → user close to known monitoring station network. Interpolation among known corrections from close reference locations.
- PPP-RTK (=SSR-RTK)** (mix between global and local approaches): transmission of PPP corrections with parallel broadcast of precise corrections on troposphere and ionosphere thanks to a dense GNSS station network. It is called the SSR concept.
 - Satellite Ephemeris Correction Parameters;
 - Satellite Time Correction Parameters;
 - Code Phase Measurement Correction Parameters;
 - Carrier Phase Measurement Correction Parameters;
 - Ionospheric Delay Correction Parameters;
 - Tropospheric Delay Correction Parameters;
 - Ranging Accuracy Information.

Table 0.2: Corrections required to support PPP, PPP-AR and SSR (or PPP)-RTK.

	PPP	PPP-AR	SSR-RTK
Satellite orbits	✓	✓	✓
Satellite clocks	✓	✓	✓
Code biases	×	✓	✓
Phase biases	×	✓	✓
Ionospheric delay	×	×	✓
Tropospheric delay	×	×	✓

Source: Thales Alenia Space & RMIT University Collaboration 1 Report of Tasks 1 and 2 (PPP-AR=PPP-Ambiguity Resolution)

EXAMPLE OF QZSS CLAS (CENTIMETER LEVEL AUGMENTATION SERVICE)

/// Based on RTCM format – SSR concept

Classical PPP for dual receivers

- Correction of orbits, clocks and biases




Precise correction of ionosphere (with STEC) and troposphere

/// Use of PPP-RTK

/ Principle:

- Classical PPP with delta corrections with respect to navigation message parameters (orbit, clock, biases)
- RTK layer: additional regional corrections of ionosphere and troposphere (grid model per sub-region) → user interpolation required

SUMMARY OF PRECISE POSITIONING METHODS




OSR = Observation State Representation
 SSR = Space State Representation
 VRS = Virtual Reference Station
 FKP = Flat Correction Parameter (in german)
 MAC = Master Auxiliary Concept
 RTK = Real-Time Kinematic
 PPP = Precise Point Positioning
 IAR = Integer Ambiguity Resolution

HYBRIDIZATION – SENSOR FUSION

/// If the GNSS signal is not available, in-situ sensors should take over

/// Typically in harsh environment (city with very high buildings, tunnels, ...)

/// Example of sensors: IMU, Odometer, Radar, Lidar, Camera, ...





IMU, Odometer, Radar, Lidar, Camera → for positioning

GNSS LEO CONSTELLATION

/// **New dissemination capabilities** -> LEO satellites serve as a complementary network to enhance (in speed or volume) the dissemination of classical services associated with the use of MEO GNSS.

/// **System Performance improvements** -> LEO satellites perform on-board GNSS measurements and act as “flying stations”. The gain in additional observables improve the quality of the orbit determination process for the classical MEO GNSS services

/// **New signals for users** -> LEO satellites are capable of broadcasting a positioning service associated with their own orbits, clocks, corrections, etc., just like the current MEO GNSS.



THANK YOU FOR YOUR ATTENTION



PROPRIETARY INFORMATION

This document is not to be reproduced, modified, adapted, published, translated in any material form in whole or in part nor disclosed to any third party without the prior written permission of Thales Alenia Space.
© 2024 Thales Alenia Space All rights reserved

THALES ALENIA SPACE LIMITED DISTRIBUTION